



17K GVWR Tilt Trailers

Available in 82x18, 82x20, 82x22, 82x24

Specifications:

Axles	(2) Dexter 8K Axles with Easy lube hubs and Electric Brakes on each axle	Electric Plug	7-Way RV
Jack	12,000# Side Wind Drop Leg	Hitch Type	Bumper Pull
Tires	215/75R17.5	Main Frame	6" Channel
Floor	2" Pressure Treated wood, Optional Metal Floor	Suspension	Heavy-Duty Multi-Leaf Spring with Equalizer
Finish	Primer and Paint	DeckTop Rail	Rub Rail with Stake Pockets
Lights	Sealed LED, D.O.T. Approved	Finish (prep)	Steel is cleaned to ensure a high quality finish
Tongue	6" Channel, wrapped with built in toolbox	Safety Chains	Heavy-Duty with safety latch
Coupler	Adjustable, Cast 2 5/16"	Deck Width	82" Between Fenders
Fenders	Heavy-Duty Diamond Plate Metal	Payload	13,800#
GVWR	17,000#	Crossmembers	3" Channel, 16" On Center
Ramps	None	Spare Tire Mount	Side mount
Tilt	Self-contained Hydraulic Damper Cylinder	Deck Length	14' Tilt

Additional options:

Pintle Hitch	Metal Deck	Spare Tire
Extreme Upgrade: Tube Frame	Gooseneck	D-Rings

Available in 18', 20', 22', and 24'



Jobsite Trailers
12608 E. Old US Hwy 64
Lexington, NC 27292

336-517-7155



Jobsite
 Dexter Axle
 Heavy-Duty brakes
 Heavy-Duty Suspension



Other Manufacturers Axle