



15K GVWR Tilt Trailers

Available in 82x18, 82x20, 82x22, 82x24

Specifications:

Axles	(2) Dexter 7K Axles with Easy lube hubs and Electric Brakes on each axle	Electric Plug	7-Way RV
Jack	12,000# Side Wind Drop Leg	Hitch Type	Bumper Pull
Tires	235/80R16 Load Range E	Main Frame	6" Channel
Floor	2" Pressure Treated wood, Optional Metal Floor	Suspension	Heavy-Duty Multi-Leaf Spring with Equalizer
Finish	Primer and Paint Gray or Black Available	Deck Top Rail	Rub Rail with Stake Pockets
Lights	Sealed LED, D.O.T. Approved	Finish (prep)	Steel is cleaned to ensure a high quality finish
Tongue	6" Channel, wrapped with built in toolbox	Safety Chains	Heavy-Duty with safety latch
Coupler	Adjustable, Cast 2 5/16"	Deck Width	82" Between Fenders
Fenders	Heavy-Duty Diamond Plate Metal	Payload	11,950#
GVWR	15,000#	Crossmembers	3" Channel, 16" On Center
Ramps	None	Spare Tire Mount	Side mount
Tilt	Self-contained Hydraulic Damper Cylinder	Deck Length	14' Tilt

Additional options:

Pintle Hitch	Metal Deck	Upgrade to 17,000#
Extreme Upgrade: Tube Frame	Gooseneck	Spare Tire
Available in 18', 20', 22', and 24'	GPS Tracker	D-Rings



Jobsite Trailers
12608 E. Old US Hwy 64
Lexington, NC 27292

336-517-7155

