



12K GVWR Tilt Trailers

Available in 82x18, 82x20, 82x22, 82x24

Specifications:

Axles	(2) Dexter 6K Axles with Easy lube hubs and Electric Brakes on each axle	Electric Plug	7-Way RV
Jack	8,000# Side Wind Drop Leg	Hitch Type	Bumper Pull
Tires	225/75R15	Main Frame	5" Channel
Floor	2" Pressure Treated wood, Optional Metal Floor	Suspension	Heavy-Duty Multi-Leaf Spring with Equalizer
Finish	Primer and Paint	DeckTop Rail	Rub Rail with Stake Pockets
Lights	Sealed LED, D.O.T. Approved	Finish (prep)	Steel is cleaned to ensure a high quality finish
Tongue	5" Channel, wrapped with built in chain tray	Safety Chains	Heavy-Duty with safety latch
Coupler	Adjustable, Cast 2 5/16"	Deck Width	82" Between Fenders
Fenders	Heavy-Duty Diamond Plate Metal	Payload	9,000#
GVWR	12,000#	Crossmembers	3" Channel, 24" On Center
Ramps	None	Spare Tire Mount	Side mount
Tilt	Self-contained Hydraulic Damper Cylinder	Deck Length	14' Tilt

Additional options:

Pintle Hitch	Metal Deck	Spare Tire
Extreme Upgrade: Tube Frame	Gooseneck	D-Rings

Available in 18', 20', 22' and 24'



Jobsite Trailers
 12608 E. Old US Hwy 64
 Lexington, NC 27292

336-517-7155

